



UNIX Workstations Facts and Features

October 14, 2003



GXT4500P



GXT6500P



**IntelliStation
POWER 275**

Product Line	IBM® @server® pSeries® 630	IntelliStation® POWER 275
Machine type	7028-6E4	9114-275
System packaging	desktop	desktop
Microprocessor type	64-bit, POWER4™	64-bit POWER4+
# of processors/system	1 or 2	1 or 2
Clock rates available	1.2 GHz / 1.45 GHz	1.0 GHz ⁿ / 1.45 GHz
System memory (standard - maximum)	1GB - 32GB ^a	1GB - 16GB ^a
Data/instruction (L1) cache	32KB - 64KB ^b	32KB - 64KB ^b
Level 2 (L2) cache	1.5MB	1.5MB ^b
Level 3 (L3) cache	8MB	8MB
Reliability, availability, serviceability		
Chipkill™ memory	X	X
Service processor	X	X
Hot-swappable disks (internal and external)	X	X
Dynamic Processor Deallocation	X	X
Hot-plug slots	X	-
Redundant hot-plug power	O	O
Redundant hot-plug cooling	X ^f	X
Capacity		
Maximum logical partitions	3	-
Maximum PCI slots	6 (64-bit)	6 (2 32-bit, 4 64-bit)
Maximum PCI bus speed (MHz)	133	133
Disk media bays	4 2	4 3
Minimum maximum internal disk storage	36.4GB 587.2GB	36.4GB 587.2GB
Ethernet ports	2 - 10/100	1 - 10/100; 1 - 10/100/1000
Storage interfaces		
#6206/6204 Ultra SCSI SE / Differential - PCI	X	X
#6203 2-channel Ultra3 SCSI - PCI	X	X
#5710/5712 2-channel Ultra320 SCSI - PCI-X	X	X
#5703/5711 2-channel Ultra320 RAID - PCI-X	X	X
#6230 SSA Advanced SerialRAID Plus	X	X
#6228 2 Gigabit Fibre Channel - PCI	X	-
#6239 2 Gigabit Fibre Channel - PCI-X	X	X
Communications and connectivity		
EIA RS232D	X	X
Token-Ring 4/16 Mbps	X	X
4-port 10/100 Mbps Ethernet	X	X
10/100 Mbps Ethernet PCI II	X	X
10/100/1000 Mbps Base-TX Ethernet PCI-X	X	X
Gigabit Ethernet (Fibre UTP)	X X	X X
Gigabit Ethernet -SX PCI-X	X	X
64-bit ATM 155 Mbps (Fibre UTP)	X X	X X
ATM 622 Mbps (Fibre)	X	X
HiPPI ^k	X	-
Quad Digital Trunk Telephony PCI ^k	X	-
X.25 ^k	X	X
SDLC	X	-
BSC	X	-
e-business Cryptographic Accelerator	X	X
PCI Cryptographic Coprocessor (FIPS-4)	X	-
Audio PCI Adapter for Workstations	X	X
Graphics accelerators	GXT135P, GXT4500P, GXT6500P	GXT135P, GXT4500P, GXT6500P
Benchmarks	(1, 2-way; 1.45 GHz)	(1, 2-way; 1.45 GHz)
SPECint_base2000	884	883
SPECfp_base2000	1,097	1,129
SPECint_rate_base2000	-	-, 18.0
SPECfp_rate_base2000	-	-, 19.6

X = Available

^a - Shared memory

^b - Per processor

^f - Optional on 1.2 GHz systems

^k - Requires additional software; check on availability

ⁿ - Only available as a 1-way system

I/O device options	pSeries 630	IntelliStation POWER 275
Disk drives and subsystems		
7204-518/536/574 External Disk Drive	X	X
7133-D40/T40 Serial Disk System	X	X
7140-160 SAN Controller	-	-
2104-DU3/TU3 Expandable Storage Plus	X	X
2104-DS4/TS4 Expandable Storage Plus U320	X	X
2105-F10/F20 Enterprise Storage Server™	X	X
5194-25T NAS 200	X	X
5196-G27 NAS Gateway 300	X	X
FAStT200/600/700/900 Storage Servers	X	X
Fibre Channel directors, switches and hubs		
2031-032/224/232 McDATA Fibre Channel Switch	X	X
2032-064/140 McDATA Fibre Channel Director	X	X
2042-128/256 INRANGE FC/9000 Fibre Channel Director	X	X
2062-D01/D02/T07 Cisco Fabric Switch / Director	X	-
3534-F08 SAN Switch	X	-
2109-F16/F32 SAN Switch	X	X
Optical drives and libraries		
7210-025 DVD-RAM Drive	X	X
4.7GB DVD-RAM Drive (internal)	X	X
16X/48X IDE DVD-ROM Drive (Internal)	X	X
Tape drives and libraries		
7205-550 External DLT Drive	X	X
7206-220/VX2 4 mm Tape Drive	X	X
7207-122/330 4GB ¼-inch External Cartridge Tape Drive	X	X
7208 External 8 mm Tape Drive	X	X
3494 Enterprise Automated Tape Library	X	X
3575 Magstar® Tape Library Dataserver	X	X
3580 Ultrium Tape Drive	X	X
3581 Ultrium Tape Autoloader	X	X
3582 Ultrium Tape Library	X	X
3583 Ultrium Scalable Tape Library	X	X
3584 UltraScalable Tape Library	X	X
3590 Enterprise Tape Drive	X	X
3592 Enterprise Tape Drive	X	X
7332-220 4 mm DDS-3 Tape Autoloader	X	X
20GB/40GB 4 mm Tape Drive (internal)	X	X
60/150GB 8 mm Tape Drive (internal)	X	X
80/160GB VXA Tape Drive (internal)	X	X

X = Available

Note: For the devices listed, not all models are supported on all systems. For more information, contact your IBM marketing representative or IBM Business Partner.

Standard warranty ¹	pSeries 630	POWER 275
9x5 next-business-day	X	-
9x5 next-business-day with CRU (customer replaceable units)	-	X

¹ These warranty terms and conditions are for the United States and may be different in other countries. Consult your local IBM representative or IBM Business Partner for country-specific information.

Workstation UNIX® performance (with AIX 5L™ v5.1) ¹	IntelliStation POWER 275 1-way (1.45 GHz)		IntelliStation POWER 275 2-way (1.45 GHz)	
	GXT4500P	GXT6500P	GXT4500P	GXT6500P
Graphics accelerators				
CATIA benchmarks	*	*	*	*
Graper423	19.67	19.28	21.96	19.25
CATIA423_CPU	21.12	21.21	-	-
CATIA423_Cover (sec) **	0.0429	0.0383	0.0281	0.0382
CATIA423_ENGINE (sec) **	0.0337	0.0342	0.0286	0.0343
CATIA423_SAG_CYL	28.51	26.5	32.99	26.58
Graper424	19.47	19.31	21.99	19.35
CATIA424_CPU	20.02	20	**	**
CATIA424_Cover (sec) **	0.042	0.0384	0.0279	0.0382
CATIA424_ENGINE (sec) **	0.033	0.0342	0.0282	0.0339
CATIA424_SAG_CYL	28.48	26.39	32.82	26.53
CATIAV5R8_HOLLAND (sec) **	49.31	45.21	43.69	39.26

* - Using AIX 5L v5.1.0.50

** - Benchmark measurement time in seconds; therefore, a smaller number means better performance

¹ This benchmark data was published July 31, 2003

System software	pSeries 630	IntelliStation POWER 275
<u>Operating system support</u>		
AIX 5L v5.1 (5765-E61)	X	X
AIX 5L v5.1 LPAR	X	-
AIX 5L v5.2 (5765-E61)	X	X
AIX 5L v5.2 dynamic LPAR	X	-

X = Available or standard feature

IBM services

IBM services provide the capabilities and solutions needed to manage virtually every aspect of an open systems environment and at any level chosen. They complement the support already included with IBM @server pSeries systems. IBM world-class services and support allow you to better manage resources and focus on what matters most – your business.

IBM customer financing provides an additional incentive. An array of attractive and flexible financing programs eases the acquisition of new technology and helps protect from the risk of obsolescence. Financing may be available to credit-qualified customers. Rates are based on credit rating, financing terms, and other options. Other restrictions may apply.

Project support services

- Operating system porting/conversion
- Operating system migration assistance
- Systems integration
- IBM and non-IBM software customization
- IBM application development
- Site planning services

Continuing support services

- Customer Support Center services
 - ✓ Electronic/voice
 - ✓ IBM and non-IBM hardware and software
- On-site software maintenance support
- Capacity planning
- Maintenance services, including multivendor environment
- Technical/application specialists
- Network custom services
- Education

Benchmark notes:

The benchmark information contained herein is current as of July 31, 2003.

Values shown in the performance benchmarks section were derived using particular, well-configured, development-level computer systems, and used 32-bit applications and external cache if external cache is supported on the system. All performance benchmark values and estimates are provided "AS IS" and no warranties or guarantees are expressed or implied by IBM. Buyers should consult other sources of information, including system benchmarks, to evaluate the performance of a system they are considering. Actual system performance may vary and is dependent upon many factors including system hardware configuration and software design and configuration. IBM recommends application-oriented testing for performance predictions. Additional information about the performance benchmarks, values, and systems tested is available from your IBM marketing representative or IBM Authorized Reseller or access the following on the Web:

SPEC – <http://www.spec.org>

Unless otherwise indicated, new or upgraded systems were tested with AIX 5L Version 5.1.

More information

- Contact your IBM marketing representative or IBM Business Partner.
- Access the pSeries Products and Services page¹ on IBM's World Wide Web server, and then select the appropriate hardware or software option.
- Product announcement letters containing more details on hardware and software offerings are available at <http://www.ibm.com/ibmlink>.
- More detailed benchmark and performance information is available at http://www.ibm.com/servers/eserver/pseries/hardware/system_perf.html



© IBM Corporation 2003

IBM Corporation
Marketing Communications
Systems Group
Route 100
Somers, New York 10589

Produced in the United States of America
10-03
All Rights Reserved

This document was developed for products and/or services offered in the United States. IBM may not offer the products, features, or services discussed in this document in other countries. The information may be subject to change without notice. Consult your local IBM business contact for information on the products, features and services available in your area.

All statements regarding IBM's future directions and intent are subject to change or withdrawal without notice and represent goals and objectives only.

IBM, the IBM logo, the e-business logo, the AIX 5L logo, @server, AIX 5L, Chipkill, Enterprise Storage Server, IntelliStation, Magstar, POWER4+, pSeries are trademarks or registered trademarks of International Business Machines Corporation in the United States or other countries or both. A full list of U.S. trademarks owned by IBM may be found at <http://www.ibm.com/legal/copytrade.shtml>.

UNIX is a registered trademark of the Open Group in the United States and other countries.

Other company, product, and service names may be trademarks or service marks of others.

IBM hardware products are manufactured from new parts, or new and used parts. Regardless, our warranty terms apply.

Photographs show engineering and design models. Changes may be incorporated in production models.

Copying or downloading the images contained in this document is expressly prohibited without the written consent of IBM.

This equipment is subject to FCC rules. It will comply with the appropriate FCC rules before final delivery to the buyer.

Information concerning non-IBM products was obtained from the suppliers of these products or other public sources. Questions on the capabilities of the non-IBM products should be addressed with the suppliers.

All performance information was determined in a controlled environment. Actual results may vary. Performance information is provided "AS IS" and no warranties or guarantees are expressed or implied by IBM.

The IBM home page on the Internet can be found at <http://www.ibm.com>.

¹ The pSeries home page on the Internet can be found at <http://www.ibm.com/servers/eserver/pseries>.

Workstations F&F - 06